

PROMAX ULTRA 5W30 C3 API SN/CF ACEA C3 12

REV.1 OF Mar /2017

LEVELS OF QUALITY

The lubricant PROMAX ULTRA 5W30 C3 complies with the following international specifications:

API SN SM/CF · ACEA C2/C3-12 · MB 229.52
 - 229.51 - 229.31 - 226.5 · BMW LONG LIFE
 04 · VW 502.00-505.00-505.01 · PORSCHE
 C30 · GM DEXOS 02 · FIAT 9.55535.S2/S3

PRODUCT DESCRIPTION

DASÖL PROMAX ULTRA 5W30 C3 is a LONG LIFE 100% synthetic lubricant with low ash content (Low SAPS) produced at the highest formulation levels, designed to provide excellent performances in modern turbocharged petrol and diesel engines complying with the new EURO IV and EURO V emission regulations.

APPLICATIONS

The modern formulation technology with low ash content allows the extension of life and maintaining the efficiency of emission reduction systems of petrol and diesel cars (DPF, TWC, FAP) unchanged.

DASÖL PROMAX ULTRA 5W30 C3 has been specifically designed to satisfy the latest ACEA C3 and C2 specifications and is recommended for motorizations fitted with particulate filtration systems, are maintenance-free and without fuel additives.

TYPICAL FEATURES*

SAE Scale		5W/30
Density at 15°C.Kg./dm3	ASTM D1298	0.850
Viscosity at 100°C.cSt	ASTM D445	11.8
Viscosity Index	ASTM D2270	150
Flammability V.A. °C	ASTM D92	216
Pour Point °C	ASTM D97	-36
S.A.	ASTM D874	0.79
T.B.N.	ASTM D2896	6.8

*The above mentioned values are indicative of production average values and are not an integral part of the specification.