

ATF DEXRON II D

REV.1 OF Mar /2017

LEVELS OF QUALITY

The lubricant ATF DEXRON II D complies with the following international specifications:

GM DEXRON IID · ZF TE-ML 02F, 03D, 04D, 09A, 11A-B, 14A, 17C · VOITH 55.6335.32 (G607) · MAN 339D · ALLISON C4 · CAT TO-2 · MB 236.1-236.7 · FORD MERCON M2C 138CJ

PRODUCT DESCRIPTION

DASÖL ATF DEXRON II D is a lubricant recommended for automatic transmissions, power steering, hydraulically assisted steering and torque convertors, whenever it is required a DEXRON II D product. It is also used as a hydraulic oil covering a large temperature range for applications in the automotive, industry and marine field.

APPLICATIONS

It ensures excellent performances in terms of:

- frictional properties;
- thermal-oxidative stability;
- wear and corrosion resistance.

Thanks to the above mentioned features it also ensures both a low pour point and a reduced foaming tendency.

TYPICAL FEATURES*

Colour		Red
Density at 15°C.Kg./dm ³	ASTM D1298	0.860
Viscosity at 100°C.cSt	ASTM D445	7.5
Viscosity Index	ASTM D2270	140
Flammability V.A.°C	ASTM D92	195
Pour Point °C	ASTM D97	-27

*The above mentioned values are indicative of production average values and are not an integral part of the specification.