

# GREEN U.T.T.O 80W / 10W30

REV.1 OF Mar /2017

## LEVELS OF QUALITY

The lubricant GREEN U.T.T.O 80W / 10W30 complies with the following international specifications:

API GL-4 · ALLISON C4 · CAT TO-2 · FORD M2C 134D · JD J20C · CNH MAT 3525-3526 · KUBOTA UDT · MF CMS M1143-M1135-M1145 · ZF TE-ML 03E , 05E · VOLVO WB101

## PRODUCT DESCRIPTION

Multifunctional lubricant (U.T.T.O. – Universal Tractor Transmission Oil) for hydraulic transmissions and systems of tractors and agricultural machineries in general.

It provides high anti-wear properties, anti-stick and anti-slip properties which allow the best effectiveness of the braking system. The high viscosity index guarantees the reaction of servo-controls under all temperature conditions.

Furthermore the formulation guarantees a reduction in power consumption and improves the efficiency of the hydraulic circuit.

## APPLICATIONS

GREEN U.T.T.O 80W / 10W30 is a multifunctional product to be used on gear changes, brake transmissions and oil bath, lateral reducers, wheel reducers, differential gears, hydraulic lifts, driving pulley, mechanical and hydrostatic guide of all agricultural machineries and earthmoving equipment, whenever a product complying with newer versions of the specification is required.

## TYPICAL FEATURES\*

SAE Scale		80W/10W30
Density at 15°C.Kg./dm <sup>3</sup>	ASTM D1298	0.870
Viscosity at 100°C.cSt	ASTM D445	10.5
Viscosity Index	ASTM D2270	135
Flammability V.A.°C	ASTM D92	205
Pour Point °C	ASTM D97	-27

\*The above mentioned values are indicative of production average values and are not an integral part of the specification.