

# PROMIX 5W40 API SL/CF ACEA A3B3

REV.1 OF Mar /2017

## LEVELS OF QUALITY

The lubricant PROMIX 5W40 API SL/CF ACEA A3/B3 complies with the following international specifications:

API SL SJ/CF · ACEA A3-B3 · VW 502.00 / 505.00 · MB 229.1

## PRODUCT DESCRIPTION

DASÖL PROMIX 5W40 API SL/CF ACEA A3/B3 is a synthetic-based multigrade oil for petrol and diesel engines able to satisfy the requirements of new concept supercharged engines and useful for the use in catalysed engines fuelled with LPG.

The high viscosity index allows use under any climatic conditions (low and high external temperatures).

It provides the maximum protection for engines and guarantees the right viscosity under any operating conditions (cold starts, long distances, etc.).

It is recommended to always observe the oil change interval as suggested by the car manufacturer.

## TYPICAL FEATURES\*

SAE Scale		5W40
Density at 15°C.Kg./dm3	ASTM D1298	0.860
Viscosity at 100°C.cSt	ASTM D445	13.5
Viscosity Index	ASTM D2270	145
Flammability V.A.°C	ASTM D92	210
Pour Point °C	ASTM D97	-30
T.B.N.	ASTM D2896	8

\*The above mentioned values are indicative of production average values and are not an integral part of the specification.