

## PROMIX TRUCK 10W40 API CI-4/SL ACEA E3-E5-E7 A3-B4

REV.1 OF Mar /2017

### LEVELS OF QUALITY

The lubricant PROMIX TRUCK 10W40 API CI-4/SL ACEA E3-E5-E7 A3-B4 complies with the following international specifications:

ACEA E3-E5-E7 A3-B4 · API CI-4/SL · MB 228.3/229.1 · MAN M3277 · VOLVO VDS-3 · MTU TYPE2 · RENAULT RVI RLD-2 · CAT ECF-2 · MACK EO-M PLUS · CUMMINS CES 20077

### PRODUCT DESCRIPTION

DASÖL PROMIX TRUCK 15W40 is multigrade oil based on the latest concept synthetic technology designed to satisfy the requirements of the latest versions of supercharged diesel engines with extended oil change intervals and at low emissions with EURO3, EURO4 and EURO5 technologies. The quality of basic oils along with a reliable additive package guarantee an excellent behaviour in service with any types of diesel fuel and extended oil change intervals according to the information provided by Manufacturers.

### APPLICATIONS

DASÖL PROMIX TRUCK 15W40 can be defined as a multifunctional product to be used in all types of fleet on high speed diesel engines, in earthmoving equipment and in all supercharged DIESEL marine engines. The following benefits can be obtained, if you use this product:

- a higher engine cleaning,
- a better protection against piston ring sticking,
- a reduced bore polishing (exhaust pipe polishing),
- more protection against wear,
- extending oil change intervals.

It is recommended to observe always the oil change interval as suggested by the car manufacturer.

### TYPICAL FEATURES\*

SAE Scale		10W40
Density at 15°C.Kg./dm <sup>3</sup>	ASTM D1298	0.870
Viscosity at 100°C.cSt	ASTM D445	13.5
Viscosity Index	ASTM D2270	145
Flammability V.A.°C	ASTM D92	218
Pour Point °C	ASTM D97	-30
TBN mgKOH/g	ASTM D 2896	9

\*The above mentioned values are indicative of production average values and are not an integral part of the specification.